ProPlus™ Padded X-Over Harness





PRODUCT FEATURES

- Cross-over style front and back
- 4-point adjustment
- 2" Steel dorsal ring
- Sternum Ring for fall arrest*, positioning and rescue
 *Fall distance must be limited to no more than 2'-0"
- Adjustable leg shoulder & chest straps
- Leg and Shoulder Pads
- Shock Load Indicator
- Velcro Lanyard Retainer
- Steel Work Positioning hip rings
- Sub-pelvic Strap
- Lightweight high-strength synthetic webbing

MATERIAL SPECIFICATIONS

Webbing:

1.75" Polyester, minimum tensile strength 6,500 lbs

Hardware:

All rings plated alloy steel, powder coated, proof loaded to 3,600 lbs. min tensile 5,000 lbs. Bayonet buckles: Plated alloy steel, powder coated, spring loaded Mating buckles: Plated alloy steel, powder coated

Shipping Weight: 3.75 lbs

PERFORMANCE SPECIFICATIONS

OSHA Capacity: 400 lbs ANSI Capacity: 310 lbs

RELEVANT STANDARDS

OSHA 1910.28 and OSHA 1926.502 ANSI ANSI/ASSP Z359.11-2014

Waist Size:

XX-Small (24-32") X-Small (28-34") Small (32-40") Medium (36-44") Large (40-48") X-Large (44-52")

Made in the USA



800-727-7471 • www.sapsis-rigging.com • sales@sapsis-rigging.com 870 Bunting Lane, Bldg A, Primos PA 19018 • FAX: 215-228-0888

The 502004X ProPlus™ Padded X-Over Harness is

a general purpose, full body harness designed to meet the needs of entertainment technicians working at height. It can be used in a multitude of applications. The harness is donned by a step-thru procedure that is quick and easy.