

ProPlus™ Utility Harness



The 502008U ProPlus™ Padded Utility Harness is a general purpose, full-body fall arrest harness for use by entertainment technicians working at height.

PRODUCT FEATURES

- Adjustable leg shoulder & chest straps
- 5-point adjustment
- 2" Sliding Back Dorsal Ring
- Lightweight high-strength synthetic webbing
- Leg and Shoulder Pads
- Shock Load Indicator
- Velcro Lanyard Retainer
- Steel Work Positioning hip rings
- Sub-pelvic Strap

MATERIAL SPECIFICATIONS

Webbing:

1.75" Polyester, minimum tensile strength 6,500 lbs

Hardware:

All rings have plated alloy steel, powder coated, proof loaded to 3,600 lbs. min tensile 5,000 lbs.

Bayonet buckles: Plated alloy steel, powder coated, spring loaded

Mating buckles: Plated alloy steel, powder coated Color: Black

Shipping Weight: 3 lbs

PERFORMANCE SPECIFICATIONS

OSHA Capacity: 400 lbs

ANSI Capacity: 310 lbs

RELEVANT STANDARDS

OSHA 1910.28 and OSHA 1926.502

ANSI ANSI/ASSP Z359.11-2014

Waist Size:

XX-Small (24-32")

X-Small (28-34")

Small (32-40")

Medium (36-44")

Large (40-48")

X-Large (44-52")

Made in the USA



800-727-7471 • www.sapsis-rigging.com • sales@sapsis-rigging.com
870 Bunting Lane, Bldg A, Primos PA 19018 • FAX: 215-228-0888