

ProPlus™ 50' Self-Retracting Device (SRD)

Code: 502202

The ProPlus™ 50' SRD provides durability and confidence expected by professionals. It features a lightweight housing and short fall arrest capabilities



PRODUCT FEATURES

- Galvanized steel cable lifeline
- Dual Internal Inertia Braking System
- 2-stage, auto-locking, swivel snap hook with ¾" gate opening
- 2-stage, auto-locking suspension carabiner with 1" gate opening
- Shock Load Indicator

MATERIAL SPECIFICATIONS

Lifeline: 50' X 3/16" Ø galvanized steel cable

Housing: Cast Aluminum

Cable Drum: Aluminum Alloy

Ratchet & Brake Pawls: Bronze

Springs & Fasteners: Stainless Steel

Carabiner: Plated Alloy Steel.

Minimum Tensile Strength: 5,000 lbs.

Snap Hook: Plated Alloy Steel

Minimum Tensile Strength: 5,000 lbs.

PERFORMANCE SPECIFICATIONS

Average Arresting Force: 1,100 lbs.

Maximum Arresting Force: 1,800 lbs.

Average Fall Distance: 10 inches

Maximum Fall Distance: 54 inches

OSHA Capacity: 400 lbs.

ANSI Capacity: 310 lbs.

Shipping Weight: 20.0 Lbs.

RELEVANT STANDARDS

OSHA 1910.28 & OSHA 1926.502

ANSI Z359.14-2014, A10.32

Class "B" SRD



Made in the USA



800-727-7471 • www.sapsis-rigging.com • sales@sapsis-rigging.com
870 Bunting Lane, Bldg A, Primos PA 19018 • FAX: 215-228-0888