

ProPlus™ 13' Self-Retracting Device (SRD) with Standard Hook

Code: 502214

The ProPlus™ 13' SRD provides durability and confidence expected by professionals. It features a lightweight housing and short fall arrest capabilities.



PRODUCT FEATURES

- Synthetic webbing lifeline
- 2-stage, auto-locking, snap hook with ¾" gate opening

MATERIAL SPECIFICATIONS

Lifeline: 13' X 1" Nylon
Housing: Stainless Steel
Ratchet & Brake Pawls: Brass
Springs & Fasteners: Stainless Steel

Snap Hook: Plated alloy steel
Minimum tensile strength: 5,000 lbs.

PERFORMANCE SPECIFICATIONS

Average Arresting Force: 900 lbs.
Maximum Arresting Force: 1,800 lbs.

Average Fall Distance: 6 inches
Maximum Fall Distance: 42 inches

OSHA Capacity: 400 lbs.
ANSI Capacity: 310 lbs.

Shipping Weight: 4.3 lbs.

RELEVANT STANDARDS

OSHA 1910.28 & OSHA 1926.502
ANSI Z359.14-2014, A10.32
Class "B" SRD



Made in the USA



800-727-7471 • www.sapsis-rigging.com • sales@sapsis-rigging.com
870 Bunting Lane, Bldg A, Primos PA 19018 • FAX: 215-228-0888