

**ProPlus™ Ultra-Mini  
Self-Retracting Device (SRD)  
with Oversized Hook**

**Code: 502216R**



The ProPlus™ Ultra-Mini SRD provides durability and confidence expected by professionals. It features a lightweight housing and short fall arrest capabilities.

**PRODUCT FEATURES**

- Synthetic webbing lifeline
- 2-stage, auto-locking, rebar snap hook with 2.5" gate opening
- 2-stage, auto-locking carabiner with 1" gate opening on harness
- Shock Load Indicator

**MATERIAL SPECIFICATIONS**

**Lifeline:** 8' X 1" Dyneema & Polyester webbing lifeline

**Housing:** UV Resistant Nylon

**Web Drum:** Nylon

**Brake Pawls:** Stainless Steel

**Springs & Fasteners:** Stainless Steel

**Carabiner:** Plated Alloy Steel.

Minimum Tensile Strength: 5,000 lbs.

**Snap Hooks:** Plated Alloy Steel

Minimum Tensile Strength: 5,000 lbs

**PERFORMANCE SPECIFICATIONS**

**Average Arresting Force:** 900 lbs.

**Maximum Arresting Force:** 1,800 lbs.

**Average Fall Distance:** 6 inches

**Maximum Fall Distance:** 24 inches

**OSHA Capacity:** 400 lbs.

**ANSI Capacity:** 310 lbs.

**Shipping Weight:** 5 lbs.

**RELEVANT STANDARDS**

OSHA 1910.28 & OSHA 1926.502

ANSI Z359.14-2014, A10.32

Class "A" SRD



**Made in the USA**



800-727-7471 • [www.sapsis-rigging.com](http://www.sapsis-rigging.com) • [sales@sapsis-rigging.com](mailto:sales@sapsis-rigging.com)  
870 Bunting Lane, Bldg A, Primos PA 19018 • FAX: 215-228-0888