ProPlus[™] 11' Self-Retracting Device (SRD)

Code: 91111

The ProPlus[™] 11' SRD provides durability and confidence expected by professionals. It features a lightweight housing and short fall arrest capabilities

PRODUCT FEATURES

- Galvanized steel cable lifeline
- 2-stage, auto-locking, swivel snap hook with ³/₄" gate opening
- 2-stage, auto-locking suspension carabiner with 1" gate

opening

• Shock Load Indicator

MATERIAL SPECIFICATIONS

Lifeline: 11' X 3/16" Ø galvanized steel cable Housing: Thermoplastic & Aluminum Cable Drum: Aluminum Alloy Ratchet & Brake Pawls: Brass Springs & Fasteners: Stainless Steel Carabiner: Plated Alloy Steel. Minimum Tensile Strength: 5,000 lbs. Snap Hook: Plated Alloy Steel Minimum Tensile Strength: 5,000 lbs.

PERFORMANCE SPECIFICATIONS

Average Arresting Force: 900 lbs. Maximum Arresting Force: 1,800 lbs.

Average Fall Distance: 6 inches Maximum Fall Distance: 48 inches

OSHA Capacity: 400 lbs. ANSI Capacity: 310 lbs.

Shipping Weight: 8.0 lbs.

RELEVANT STANDARDS

OSHA 1910.28 & OSHA 1926.502 ANSI Z359.14-2014, A10.32 Class "A" SRD



Made in USA



800-727-7471 • www.sapsis-rigging.com • sales@sapsis-rigging.com 870 Bunting Lane, Bldg A, Primos PA 19018 • FAX: 215-228-0888

