

## ProPlus™ 30' Self-Retracting Device (SRD)

Code: 91130

The ProPlus™ 30' SRD provides durability and confidence expected by professionals. It features a lightweight housing and short fall arrest capabilities



### PRODUCT FEATURES

- Galvanized steel cable lifeline
- 2-stage, auto-locking, swivel snap hook with ¾" gate opening
- 2-stage, auto-locking suspension carabiner with 1" gate opening
- Shock Load Indicator

### MATERIAL SPECIFICATIONS

Lifeline: 30' X 3/16" Ø galvanized steel cable

Housing: Thermoplastic & Aluminum

Cable Drum: Aluminum Alloy

Ratchet & Brake Pawls: Brass

Springs & Fasteners: Stainless Steel

Carabiner: Plated Alloy Steel.  
Minimum Tensile Strength: 5,000 lbs.

Snap Hook: Plated Alloy Steel  
Minimum Tensile Strength: 5,000 lbs.

### PERFORMANCE SPECIFICATIONS

Average Arresting Force: 900 lbs.

Maximum Arresting Force: 1,800 lbs.

Average Fall Distance: 9 inches

Maximum Fall Distance: 54 inches

OSHA Capacity: 400 lbs.

ANSI Capacity: 310 lbs.

Shipping Weight: 10.0 Lbs.



### RELEVANT STANDARDS

OSHA 1910.28 & OSHA 1926.502

ANSI Z359.14-2014, A10.32

Class "B" SRD

Made in the USA



800-727-7471 • [www.sapsis-rigging.com](http://www.sapsis-rigging.com) • [sales@sapsis-rigging.com](mailto:sales@sapsis-rigging.com)  
870 Bunting Lane, Bldg A, Primos PA 19018 • FAX: 215-228-0888