

**ProPlus™ Dual Ultra-Mini
Self-Retracting Device (SRD)
With Oversized Hooks**

Code: 502219



The ProPlus™ Dual Ultra-Mini SRD provides durability and confidence expected by professionals. It features a lightweight housing and short fall arrest capabilities.

PRODUCT FEATURES

- Synthetic webbing lifeline
- 2-stage, auto-locking, rebar snaps with 2.5" gate opening on each leg
- 2-stage, auto-locking carabiner with 1" gate opening on harness
- Shock Load Indicator

MATERIAL SPECIFICATIONS

Lifeline: 8' X 1" Dyneema & Polyester webbing lifeline

Housing: UV Resistant Nylon

Web Drum: Nylon

Brake Pawls: Stainless Steel

Springs & Fasteners: Stainless Steel

Carabiner: Plated Alloy Steel.

Minimum Tensile Strength: 5,000 lbs.

Snap Hooks: Plated Alloy Steel

Minimum Tensile Strength: 5,000 lbs

PERFORMANCE SPECIFICATIONS

Average Arresting Force: 900 lbs.

Maximum Arresting Force: 1,800 lbs.

Average Fall Distance: 6 inches

Maximum Fall Distance: 24 inches

OSHA Capacity: 400 lbs.

ANSI Capacity: 310 lbs.

Shipping Weight: 9 lbs.

RELEVANT STANDARDS

OSHA 1910.28 & OSHA 1926.502

ANSI Z359.14-2014, A10.32

Class "A" SRD



800-727-7471 • www.sapsis-rigging.com • sales@sapsis-rigging.com
870 Bunting Lane, Bldg A, Primos PA 19018 • FAX: 215-228-0888