

## ProPlus™ 11' Self-Retracting Device (SRD)

Code: 91111

The ProPlus™ 11' SRD provides durability and confidence expected by professionals. It features a lightweight housing and short fall arrest capabilities



### PRODUCT FEATURES

- Galvanized steel cable lifeline
- 2-stage, auto-locking, swivel snap hook with ¾" gate opening
- 2-stage, auto-locking suspension carabiner with 1" gate opening
- Shock Load Indicator

### MATERIAL SPECIFICATIONS

**Lifeline:** 11' X 3/16" Ø galvanized steel cable

**Housing:** Thermoplastic & Aluminum

**Cable Drum:** Aluminum Alloy

**Ratchet & Brake Pawls:** Brass

**Springs & Fasteners:** Stainless Steel

**Carabiner:** Plated Alloy Steel.

Minimum Tensile Strength: 5,000 lbs.

**Snap Hook:** Plated Alloy Steel

Minimum Tensile Strength: 5,000 lbs.

### PERFORMANCE SPECIFICATIONS

**Average Arresting Force:** 900 lbs.

**Maximum Arresting Force:** 1,800 lbs.

**Average Fall Distance:** 6 inches

**Maximum Fall Distance:** 48 inches

**OSHA Capacity:** 400 lbs.

**ANSI Capacity:** 310 lbs.

**Shipping Weight:** 8.0 lbs.

### RELEVANT STANDARDS

OSHA 1910.28 & OSHA 1926.502

ANSI Z359.14-2014, A10.32

Class "A" SRD



800-727-7471 • [www.sapsis-rigging.com](http://www.sapsis-rigging.com) • [sales@sapsis-rigging.com](mailto:sales@sapsis-rigging.com)  
870 Bunting Lane, Bldg A, Primos PA 19018 • FAX: 215-228-0888